



SAFETY DATA SHEET GRIPDECK PRIMECOAT RESIN

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME GRIPDECK PRIMECOAT RESIN
INTERNAL ID GRIPPR/4
APPLICATION Component of Car Park Decking Repair System
SUPPLIER Don Construction Products Ltd.,
Churnetside Business Park,
Station Road,
Cheddleton,
Staffordshire ST13 7RS
For technical and non-emergency call:
phone: 01538 361799
For advice on medical emergencies,
fires, spillages or chemical hazards
phone: +44(0) 870 190 6777
Fax: 01538 361899
E-Mail: info@donconstruction.co.uk

2 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact.

CLASSIFICATION R43.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BRANCHED POLYALCOHOL WITH ESTER AND ETHER END GROUPS			35-50%	R43.
CYCLOHEXANONE	203-631-1	108-94-1	0.2-0.5%	R10 Xn;R20

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Polyalcohol with ester and ether groups containing additives.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Immediately rinse with water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Small fires: Foam, carbon dioxide or dry powder. Larger fires: Water spray.

SPECIFIC HAZARDS

In case of fire, toxic gases may be formed.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

GRIPDECK PRIMECOAT RESIN

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Use protective gloves, goggles and suitable protective clothing.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses.

SPILL CLEAN UP METHODS

Small Spillages Absorb with sand or other inert absorbent. Large Spillages Dam and absorb spillages with sand, earth or other non-combustible material. Wear necessary protective equipment. Collect spillage in steel containers, seal securely and deliver for disposal according to local regulations.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid contact with skin and eyes. Provide good ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when using the product. Do not use in confined spaces without adequate ventilation and/or respirator.

STORAGE PRECAUTIONS

Keep separate from food, feedstuffs, fertilisers and other sensitive material. Store in tightly closed original container in a dry, cool and well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
CYCLOHEXANONE	WEL	10 ppm(Sk)		20 ppm(Sk)		

WEL = Workplace Exposure Limit.

ENGINEERING MEASURES

Provide adequate ventilation.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation use a respirator suitable for organic vapours. Consult respirator manufacturer for specific advice.

HAND PROTECTION

Protective gloves should be used if there is a risk of direct contact or splash. Nitrile gloves to BSEN374 are recommended. Break through times can vary depending on thickness, use and source. Change gloves regularly.

EYE PROTECTION

If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.

OTHER PROTECTION

Wear suitable protective clothing as protection against splashing or contamination.

HYGIENE MEASURES

Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Wash contaminated clothing before reuse.

PERSONAL PROTECTION

Always check applicability with your supplier of protective equipment.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Beige.		
ODOUR	Almost odourless		
SOLUBILITY	Immiscible with water		
RELATIVE DENSITY	1.6 Approx. @20 degC	pH-VALUE, CONC. SOLUTION	N/A
VISCOSITY	50-100 approx Ps @ 20 degC	FLASH POINT (°C)	>100

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid exposure to high temperatures or direct sunlight.

GRIPDECK PRIMECOAT RESIN

HAZARDOUS DECOMPOSITION PRODUCTS

None under normal conditions.

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause some discomfort in poorly ventilated areas.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Prolonged or repeated exposure may cause some irritation of the skin. May cause sensitisation by skin contact.

EYE CONTACT

May cause temporary eye irritation.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product should not be allowed to enter drains, sewers or watercourses.

DEGRADABILITY

The product is not readily biodegradable. Fully cured product, following use, is resistant to degradation but is inert and unlikely to cause ecological effects.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Small quantities of product may be treated with an equivalent quantity of product hardener, allowed to cure and disposed of as low hazard waste.

Larger quantities should be disposed of as controlled liquid waste via a licensed waste operator.

WASTE CLASS

Waste Code for product : 080112

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

ADR CLASS

Not classified for transportation. MARINE POLLUTANT No.

15 REGULATORY INFORMATION

LABELLING



Irritant

CONTAINS

BRANCHED POLYALCOHOL WITH ESTER AND ETHER END GROUPS

RISK PHRASES

R43 May cause sensitisation by skin contact.

SAFETY PHRASES

S24 Avoid contact with skin.

S36/37 Wear suitable protective clothing and gloves.

S60 This material and its container must be disposed of as hazardous waste.

16 OTHER INFORMATION

GENERAL INFORMATION

Don Construction Products Ltd. Technical Datasheet.

REVISION COMMENTS

Changes to Sections 2, 3, 4, 7, 8, 11 & 15

GRIPDECK PRIMECOAT RESIN

REVISION DATE 10/03/09

REV. NO./REPL. SDS GENERATED 4

RISK PHRASES IN FULL

R10	Flammable.
R20	Harmful by inhalation.
R43	May cause sensitisation by skin contact.