



SAFETY DATA SHEET GRIPDECK MEDIUM AGGREGATE

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME	GRIPDECK MEDIUM AGGREGATE
INTERNAL ID	GRIPMAGG/3
APPLICATION	Aggregate
SUPPLIER	Don Construction Products Ltd., Churnetside Business Park, Station Road, Cheddleton, Staffordshire ST13 7RS For technical and non-emergency call: phone: 01538 361799 For advice on medical emergencies, fires, spillages or chemical hazards phone: +44(0) 870 190 6777 Fax: 01538 361899 E-Mail: info@donconstruction.co.uk

2 COMPOSITION/INFORMATION ON INGREDIENTS

COMPOSITION COMMENTS

Blend of inert aggregates. The product may contain a low level of respirable crystalline silica. The product does not contain any hazardous ingredients in a concentration that requires declaration in this section.

3 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

4 FIRST-AID MEASURES

INHALATION

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

INGESTION

Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Irrigate the eyes with water or proprietary eye-wash for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

The product is non-combustible.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid inhalation of dust.

SPILL CLEAN UP METHODS

Avoid dust formation. Preferably remove spillage with a vacuum cleaner. If not possible dampen with water and collect spillage with a shovel, broom or the like.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid handling which leads to dust formation. Observe good industrial hygiene practices. Do not eat, drink or smoke when using the product.

GRIPDECK MEDIUM AGGREGATE**STORAGE PRECAUTIONS**

Store in closed original container in a dry place. Keep separate from food, feedstuffs, fertilisers and other sensitive material.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION**INGREDIENT COMMENTS**

The product may contain a low level of respirable crystalline silica (WEL 0.3 mg/m³; 8 hours TWA).

General nuisance dust levels should be controlled to WEL (8hr TWA):-

10mg/m³ total inhalable dust

4mg/m³ respirable dust.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of dust.

RESPIRATORY EQUIPMENT

Wear suitable respiratory protection. A half mask dust respirator approved to EN 149 : 2001 FFP2 is recommended. Ensure that the mask fits tightly to ensure an efficient seal.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves.

EYE PROTECTION

Wear dust resistant safety goggles where there is danger of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent repeated or prolonged skin contact.

PERSONAL PROTECTION

Always check applicability with your supplier of protective equipment.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Coarse powder		
ODOUR	Odourless		
BULK DENSITY	2650 approx kg/m ³	FLASH POINT (°C)	N/A

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions and recommended use.

11 TOXICOLOGICAL INFORMATION**INHALATION**

Dust in high concentrations may irritate the respiratory system. The product may contain a small percentage of respirable crystalline silica. Prolonged exposure to dust may result in long term irreversible effects

INGESTION

Unlikely to occur in normal use. No harmful effects expected in amounts likely to be ingested by accident.

SKIN CONTACT

Prolonged or repeated exposure may cause some irritation of the skin.

EYE CONTACT

May cause temporary eye irritation.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

The product is not expected to be hazardous to the environment.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Small quantities may be disposed of as low hazard waste. Larger quantities should be disposed of as controlled waste by a licensed waste operator.

WASTE CLASS

Waste Code for Product : 160304

14 TRANSPORT INFORMATION

GRIPDECK MEDIUM AGGREGATE

GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).		
	No transport warning sign required.		
ADR CLASS	Not classified for transportation.	MARINE POLLUTANT	No.

15 REGULATORY INFORMATION

RISK PHRASES	NC	Not classified.
SAFETY PHRASES	NC	Not classified.

16 OTHER INFORMATION

INFORMATION SOURCES

Health and Safety Executive Guidance Note EH40 (amended annually). Workplace Exposure Limits. Respirable crystalline silica is subject to a Chemicals Hazard Alert Notice (CHAN) Number 35. Text can be found at <http://www.hse.gov.uk/pubns/chan35.htm>.

REVISION COMMENTS

Section 1: Addition of emergency telephone number. Section 8 : Improved PPE information. Section 13: Addition of waste codes.

Section 8: WEL update.

REVISION DATE 19/05/06

REV. NO./REPL. SDS GENERATED 3